

# Saving Date/Time Fields with the TestTrack SDK Changes the GMT Offset

If you use the TestTrack SDK, and save the date in a date/time field, it looks like the GMT offset changes. However, the offset does not actually change. The time being sent back is technically the same time, but it is automatically adjusted to the local time zone with Daylight Saving Time.

For example, using saveDefect, you change the date from 10/10/2007 to 1/1/2007.

The following:

```
<item xsi:type="ttns:CDateTimeField" SOAP-ENC:position="[1]">
  <recordid>335</recordid>
  <name>CustomDateTime</name>
  <value>2001-10-01T10:10:10-04:00</value>
</item>
```

is changed to:

```
<item xsi:type="m:CDateTimeField" SOAP-ENC:position="[1]">
  <recordid>335</recordid>
  <name>CustomDateTime</name>
  <value>2001-01-01T10:10:10-04:00</value>
</item>
```

When you get the information again, using the TestTrack Client or the TestTrack SDK, the time is different and the offset is changed. For example:

```
<item xsi:type="ttns:CDateTimeField" SOAP-ENC:position="[1]">
  <recordid>335</recordid>
  <name>CustomDateTime</name>
  <value>2001-01-01T09:10:10-05:00</value>
</item>
```

TestTrack Client users cannot see that the offset changed, so it appears to be a completely different time.

---

Article ID: 344

Last updated: 31 Dec, 2014

Revision: 3

Helix ALM (formerly TestTrack) -> Saving Date/Time Fields with the TestTrack SDK Changes the GMT Offset

<http://www.seapine.com/knowledgebase/index.php?View=entry&EntryID=344>