

# Helix ALM Unix Default Directories, Commands, and Configuration Files

Following are the default directories, commands, and configuration files for Helix ALM applications running on Linux and Mac.

## Linux

### Desktop client

- Application directory - /var/lib/HelixALM
- To start - /usr/bin/ttclient

### Integration library

- 32-bit Linux - /usr/lib/seapine/tt (libraries also installed in the /usr/lib)
- 64-bit Linux - /usr/lib/seapine/tt64

### Web client

- Login URL - <https://localhost/ttweb/index.html#Default>
- CGI directory - /var/www/cgi-bin
- HTML files directory - /var/www/html/ttweb

## Server

- Server port - 1566
- Startup log - /var/log/Startup.log
- Application directory - /var/lib/HelixALM
- To start - /usr/bin/ttstudio start
- To stop - /usr/bin/ttstudio stop

### Desktop server admin utility

- Application directory - /var/lib/HelixALM
- To start - /usr/bin/ttadmin

### Web server admin utility

- Login URL - <https://localhost/ttweb/ttadmin/adminlogin.htm>
- CGI directory - /var/www/cgi-bin
- HTML files directory - /var/www/html/ttweb/ttadmin

## SDK

- CGI URL - <https://localhost/cgi-bin/ttsoapcgi.exe>
- CGI directory - /var/www/cgi-bin
- SOAP WSDL (ttsoapcgi.wsdl) directory - /var/www/html

## Registry utility

- Application directory - /var/lib/HelixALM
- To start - /usr/bin/ttregutil

## Source control provider CGI

- CGI URL - <https://localhost/cgi-bin/tttextpro.exe>
- CGI directory - /var/www/cgi-bin

## Published data CGI

- CGI URL - <https://localhost/cgi-bin/ttpubdata.exe>
- CGI directory - /var/www/cgi-bin

## Mac

### Desktop client

- Application directory - /Applications/HelixALM
- To start - Double-click icon in Applications/HelixALM

### Integration library

Directory - /Library/Application Support/Seapine/TestTrackIntegration.framework

### Desktop server admin utility

- Application directory - /Applications/HelixALM
- To start - Double-click icon in Applications/HelixALM

**Note:** The following information only applies to TestTrack 2015.1.1 or earlier. TestTrack Server, CGI, SDK, and registry utility support on Mac was discontinued in the 2016 release.

### Web client

- Login URL - <https://localhost/ttweb/index.html#Default>
- CGI directory - /Library/WebServer/CGI-Executables
- HTML files directory - /Library/WebServer/Documents/ttweb

## Server

- Server port - 1566
- Startup log - /var/log/Startup.log
- Application directory - /Applications/TestTrack
- To start - Use System Preferences
- To stop - Use System Preferences

## Web server admin utility

- Login URL - <https://localhost/ttadmin/adminlogin.htm>
- CGI directory - /Library/WebServer/CGI-Executables
- HTML files directory - /Library/WebServer/Documents/ttweb/ttadmin

## SDK

- CGI URL - <https://localhost/cgi-bin/ttsoapcgi.exe>
- CGI directory - /Library/WebServer/CGI-Executables
- SOAP WSDL (ttsoapcgi.wsdl) directory - Library/WebServer/Documents

## Registry utility

- Application directory - /Applications/TestTrack
- To start - Double-click icon in Applications/TestTrack

## Source control provider CGI

- CGI URL - <https://localhost/cgi-bin/tttextpro.exe>
- CGI directory - /Library/WebServer/CGI-Executables

## Published data CGI

- CGI URL - <https://localhost/cgi-bin/ttpubdata.exe>
- CGI directory - /Library/WebServer/CGI-Executables

## TestTrack Pro Web 2013.0 and earlier

Login URL - <https://localhost/ttweb/login.html>

## Linux

- CGI directory - /var/www/cgi-bin
- HTML files directory - /var/www/html/ttweb

## Mac

- CGI directory - /Library/WebServer/CGI-Executables
- HTML files directory - /Library/WebServer/Documents/ttweb

## TestTrack RM Reviewer 2013.0 and earlier

Login URL - <https://localhost/rmweb/index.html>

## Linux

- CGI directory - /var/www/cgi-bin
- HTML files directory - /var/www/html/rmweb

## Mac

- CGI directory - /Library/WebServer/CGI-Executables
- HTML files directory - /Library/WebServer/Documents/rmweb

## TestTrack TCM Test Runner 2013.0 and earlier

Login URL - <https://localhost/ttweb/tcmlogin.html>

## Linux

- CGI directory - /var/www/cgi-bin
- HTML files directory - /var/www/html/ttweb

## Mac

- CGI directory - /Library/WebServer/CGI-Executables
- HTML files directory - /Library/WebServer/Documents/ttweb

## Configuration files

- ttadminclient.conf - Used by the TestTrack 2013.0 and earlier Server Admin Utility. Contains information specific to the admin utility, such as the help file directory location. Located in /etc.
- ttclient.conf - Used by the Helix ALM Server Admin Utility and Helix ALM Client. Contains information such as the configured server connections and default browser settings. Located in /etc and the .seapine directory in the user's home directory.
- ttmainclient.conf - Used by the Helix ALM Client. Contains window positions, the last logged in user, and other information. Located in the .seapine directory in the user's home directory.
- ttstudio.conf - Used by the Helix ALM Server. Contains the server port number, HTML forms path, and other information. Located in /etc.

---

Article ID: 445

Last updated: 27 Jul, 2017

Revision: 10

Helix ALM (formerly TestTrack) -> Helix ALM Unix Default Directories, Commands, and Configuration Files

<http://www.seapine.com/knowledgebase/index.php?View=entry&EntryID=445>