

# Helix ALM Unix Default Directories, Commands, and Configuration Files

Following are the default directories, commands, and configuration files for Helix ALM applications running on Linux and Mac.

## Linux

### Desktop client

- Application directory - `/var/lib/HelixALM`
- To start - `/usr/bin/ttclient`

### Integration library

- 32-bit Linux - `/usr/lib/seapine/tt` (libraries also installed in the `/usr/lib`)
- 64-bit Linux - `/usr/lib/seapine/tt64`

### Web client

- Login URL - `https://localhost/ttweb/index.html#Default`
- CGI directory - `/var/www/cgi-bin`
- HTML files directory - `/var/www/html/ttweb`

### Server

- Server port - 1566
- Startup log - `/var/log/Startup.log`
- Application directory - `/var/lib/HelixALM`
- To start - `/usr/bin/ttstudio start`
- To stop - `/usr/bin/ttstudio stop`

### Desktop server admin utility

- Application directory - `/var/lib/HelixALM`
- To start - `/usr/bin/ttadmin`

### Web server admin utility

- Login URL - `https://localhost/ttweb/ttadmin/adminlogin.htm`
- CGI directory - `/var/www/cgi-bin`
- HTML files directory - `/var/www/html/ttweb/ttadmin`

### SDK

- CGI URL - `https://localhost/cgi-bin/ttsoapcgi.exe`

- CGI directory - /var/www/cgi-bin
- SOAP WSDL (ttsoapcgi.wsdl) directory - /var/www/html

## Registry utility

- Application directory - /var/lib/HelixALM
- To start - /usr/bin/ttregutil

## Source control provider CGI

- CGI URL - https://localhost/cgi-bin/ttextpro.exe
- CGI directory - /var/www/cgi-bin

## Published data CGI

- CGI URL - https://localhost/cgi-bin/ttpubdata.exe
- CGI directory - /var/www/cgi-bin

## Mac

### Desktop client

- Application directory - /Applications/HelixALM
- To start - Double-click icon in Applications/HelixALM

### Integration library

Directory - /Library/Application Support/Seapine/TestTrackIntegration.framework

### Desktop server admin utility

- Application directory - /Applications/HelixALM
- To start - Double-click icon in Applications/HelixALM

**Note:** The following information only applies to TestTrack 2015.1.1 or earlier. TestTrack Server, CGI, SDK, and registry utility support on Mac was discontinued in the 2016 release.

### Web client

- Login URL - https://localhost/ttweb/index.html#Default
- CGI directory - /Library/WebServer/CGI-Executables
- HTML files directory - /Library/WebServer/Documents/ttweb

### Server

- Server port - 1566

- Startup log - /var/log/Startup.log
- Application directory - /Applications/TestTrack
- To start - Use System Preferences
- To stop - Use System Preferences

## **Web server admin utility**

- Login URL - <https://localhost/ttweb/ttadmin/adminlogin.htm>
- CGI directory - /Library/WebServer/CGI-Executables
- HTML files directory - /Library/WebServer/Documents/ttweb/ttadmin

## **SDK**

- CGI URL - <https://localhost/cgi-bin/ttsoapcgi.exe>
- CGI directory - /Library/WebServer/CGI-Executables
- SOAP WSDL (ttsoapcgi.wsdl) directory - Library/WebServer/Documents

## **Registry utility**

- Application directory - /Applications/TestTrack
- To start - Double-click icon in Applications/TestTrack

## **Source control provider CGI**

- CGI URL - <https://localhost/cgi-bin/tttextpro.exe>
- CGI directory - /Library/WebServer/CGI-Executables

## **Published data CGI**

- CGI URL - <https://localhost/cgi-bin/ttpubdata.exe>
- CGI directory - /Library/WebServer/CGI-Executables

## **TestTrack Pro Web 2013.0 and earlier**

Login URL - <https://localhost/ttweb/login.html>

## **Linux**

- CGI directory - /var/www/cgi-bin
- HTML files directory - /var/www/html/ttweb

## **Mac**

- CGI directory - /Library/WebServer/CGI-Executables
- HTML files directory - /Library/WebServer/Documents/ttweb

## TestTrack RM Reviewer 2013.0 and earlier

Login URL - <https://localhost/rmweb/index.html>

### Linux

- CGI directory - /var/www/cgi-bin
- HTML files directory - /var/www/html/rmweb

### Mac

- CGI directory - /Library/WebServer/CGI-Executables
- HTML files directory - /Library/WebServer/Documents/rmweb

## TestTrack TCM Test Runner 2013.0 and earlier

Login URL - <https://localhost/ttweb/tcmlogin.html>

### Linux

- CGI directory - /var/www/cgi-bin
- HTML files directory - /var/www/html/ttweb

### Mac

- CGI directory - /Library/WebServer/CGI-Executables
- HTML files directory - /Library/WebServer/Documents/ttweb

## Configuration files

- ttadminclient.conf - Used by the TestTrack 2013.0 and earlier Server Admin Utility. Contains information specific to the admin utility, such as the help file directory location. Located in /etc.
- ttclient.conf - Used by the Helix ALM Server Admin Utility and Helix ALM Client. Contains information such as the configured server connections and default browser settings. Located in /etc and the .seapine directory in the user's home directory.
- ttmainclient.conf - Used by the Helix ALM Client. Contains window positions, the last logged in user, and other information. Located in the .seapine directory in the user's home directory.
- ttstudio.conf - Used by the Helix ALM Server. Contains the server port number, HTML forms path, and other information. Located in /etc.

---

Article ID: 445

Last updated: 28 Jul, 2017

Revision: 11

Helix ALM (formerly TestTrack) -> Helix ALM Unix Default Directories, Commands, and Configuration Files

<http://www.seapine.com/knowledgebase/index.php?View=entry&EntryID=445>