

Configuring the Server Database Location for Surround SCM 4.0-2008.1

Note: The following information only applies to Surround SCM 4.0-2008.1.

Surround SCM includes two registry entries that allow users to configure the location of the Surround SCM Server database. You may want to move the databases to another disk or directory for security reasons or backup purposes.

The default Surround SCM Server database location is applicationdir/SCMServDb. For example:

C:\Program Files\Seapine\Surround SCM\SCMServDb (Windows)

The default Surround SCM repository location is applicationdir/SCMServDb/SCMRepos. For example:

C:\Program Files\Seapine\Surround SCM\SCMServDb\SCMRepos. (Windows)

Keep the following in mind:

- You must manually add the entries to the registry.
- You must stop and restart the Surround SCM Server for the options to take effect.
- We strongly recommend that you back up all Surround SCM data before you add the registry entries.
- You must move any directories that were originally created in the default SCMRepos location to the new location. They will not load correctly if you do not move them.

Windows

1. Add the following registry entry to change the default Surround SCM Server database location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Seapine Software\Surround SCM\SCM  
Server\ApplicationServerDbDirectory
```

This entry overrides the default location of applicationdir/SCMServDB with the defined value.

2. Add the following registry entry to change the default Surround SCM repositories location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Seapine Software\Surround SCM\SCM  
Server\ApplicationRepoDbDirectory
```

This entry overrides the default location of applicationdir/SCMServDB/SCMRepos with the defined value.

Unix

Add the following entries to the etcspscm.conf configuration file:

- ApplicationServerDbDirectory:
- ApplicationRepoDbDirectory:

Examples:

/Applications/SurroundSCM/SCMServDb/SCMRepos (Mac)

/var/lib/SurroundSCM/SCMServDb/SCMRepos (Linux)

Note: If you do not define an ApplicationRepoDbDirectory it defaults to ApplicationServerDbDirectory/SCMRepos.

Article ID: 612

Last updated: 30 Apr, 2015

Revision: 5

Surround SCM -> Configuring the Server Database Location for Surround SCM 4.0-2008.1

<http://www.seapine.com/knowledgebase/index.php?View=entry&EntryID=612>